

Product manual

 URL: <http://www.hydro-sky.co.jp>
 Email: hydro@hydro-sky.co.jp
HydroSky Co.,Ltd.
 4-11-9,Narihira,Sumida-Ku,Tokyo,Japan
 TEL. : +81-3-5637-8834 FAX. : +81-3-5637-8874

HYDROSKY SKY-Coat Fiber



- [Application] Cloth, paper (magazine, newspaper, cardboard, etc.), other such as xylem, also effective on tiles and tub, of addition to the car of metal such as stainless steel glass and body in the bathroom.
1. Generic name High-performance super water repellent
 2. Standards Company standard
 3. Features Super water-repellent agent was able. Usage is unknown. I will reveal the super water-repellent. Water-repellent effect of surprise will appear after the coated dry cloth or paper. The applied it is also will likely forget. It does not give any change in the sense of material. It is possible to use in a variety of applications. Easily water-repellent is I now can on their own. Durability unabated of even wash also clothing such as many times effect also high, water-repellent effect will continue to persist.

GHS label elements
picture
display or symbol:



4. General properties	
Item	The contents
Principal component	Alkoxide + ethanol+ isopropyl alcohol
Contents appearance	1-component
Packing	18 liters(14kg)
Color phase	Colorless transparent or milky color
Light Sawa	After drying, the texture of the base is not changed at all
Specific gravity	0.75~0.95 (20°C)
Viscosity	10mPa·s les.
pH	No data
Boiling point	50~82°C
Melting point	-88.5°C
Flash point	11.7 °C (sealed) 21.0 °C (open type)
Ignition point	480°C
Odor	Solvent odor
Solubility	There hydrolyzable
Solubility	Water, alcohols, ethers, acetone most other organic solvents miscible

5. Paint standard	
Item	The contents
Protection	I basically protection
Wash	When using the cleaning agent, and a good wash. Cleaning is desirable for finishing the appearance, and to sufficiently dry when it is washed with water.
Coating cloth	Coating amount is .08-.35 liters per square meter. Roller, brush, I painted average in the sprayer.Coating amount varies depending on the underlying. Construction place, by site to select the applicator.
Dry	As dry long, strength increases.

6. Related law	
Hazardous materials display	Hazardous materials fourth class alcohol (water-soluble) risk grade 2
Solvent classification	Second one organic solvent
Hazardous substances display	Enforcement Ordinance Appendix to the first of two non-hazardous substances
Deleterious substance display	Not applicable

7. Precautions [Warning]

And wiping completely because advance if the application of the Hydro-Sky SKY-SP (neutralization deterrence-efflorescence processing purposes) react strongly with the components of the SKY-SP.

8. Notes on construction

1. white even while Heritage plus it is applied to the material with water absorption The whitening does not but, granite, etc., hard surface of the material surplus after application Portion beautiful finishing those who wiped off with a dry cloth.
2. Concrete and stone, the method of applying such as bricks I do not particularly wish, vertical, then horizontal and cross is applied to the average.
3. Deep portion of the joint By squeezing a roller, there is a case in which the coating plaques appear. Also, when it remains to adhere to the sealing agent to stand, which causes stains future melt the sealant.
4. Heritage Plus repellent water even immediately after application. After drying, because if watering the construction surface to water absorption is applied shortage, please apply again.
5. Please fill up quickly after opening.
Please remaining material after opening it up on the cause air and chemically react in the container. In the case of short-term storage to like moisture, dust is not mixed, sealed lid, please keep in the place where it is not out of reach of children. Do not particularly returned the use residue in original container also.
6. Should, washed with a large amount of water if it gets into your eyes, I ask that you consult your doctor.